



Mansion Close
Moulton Park
Northampton, NN3 6RU
Emergency Contact No:
0800 8405505

Date of issue SDS: 29/09/09
Review date SDS:
SDS Version: 1.1
MSDS Ref : 28

Sprayway 955 Anti Static Spray (554ml)

1. Identification of the Substance/Preparation and of the Company/Undertaking

1.1 Identification of the substance or preparation

Trade Name : Sprayway 955 Anti-Static (554ml)
Product Code : SDSASSPY

1.2 Company identification

Name : TPS
Company Role : Distributor
Street : Mansion Close Moulton Park
City : Northampton
Country : England
Website : www.totalprintsupplies.co.uk

1.3 Emergency telephone number

Emergency Number : 0800 840 5505 (office hours only)

2. Hazards Identification

2.1 Classification and general Hazards

Extremely flammable
Avoid contact with skin and eyes
Use only in well-ventilated areas

3. Composition/Information on Ingredients

3.1 Description : A mixture of Ethyl Alcohol (64-17-5), Diethyl Ammonium Chloride (68132-96- 7), Nonylpenoxpoly Ethanol (75-21-8) and propellant

3.2 Propellant : Liquefied Petroleum Gas (C.A.S. 68476-85-7)

3.2. Dangerous components : Contains 73 % Ethyl Alcohol and 25 % Liquefied Petroleum Gas.

Sprayway 955 Anti Static Spray (554ml)

Unidentified ingredients are not considered hazardous.

4. First-Aid Measures

4.1 Effects and symptoms

No additional information available

4.2 First Aid Measures

- | | |
|------------------------------|---|
| In case of contact with eyes | : Rinse immediately with plenty of water for 15 minutes, holding eyelids open and seek medical advice if irritation persists. |
| In case of skin contact | : Take off immediately all contaminated clothing. Wash skin with large amounts of soap and water. Seek medical advice if irritation persists. |
| In case of inhalation | : Remove the victim to fresh air. Provide Oxygen if breathing is difficult. Give artificial respiration if not breathing. Seek medical advice. |
| In case of ingestion | : Rinse out mouth with water. If victim is conscious and able to swallow, have victim drink water or milk to dilute. Never give anything by mouth if victim is unconscious. Do not smoke. Do not stimulate vomiting. Seek medical advice. |

4.3 Medical advice

No additional information available

5. Fire-Fighting Measures

5.1. Flammable Limits

(% Volume in air) (Propellant) : LEL : 1.8 – UEL : 9.2

5.2. Special exposure hazards

- : Heating will cause pressure rise with risk of bursting. Bursting aerosols can be forcibly projected from a fire. Keep containers cool by spraying with water if exposed to fire. Keep public away from danger area. If possible, remove to a safe, ventilated place

5.3 Extinguishing agents

: CO₂, foam and/or dry chemical
Extinguishing media which must not be used for safety reasons : full jet of water.

Sprayway 955 Anti Static Spray (554ml)

5.4 Personal protection

Special protective equipment for fire-fighters

- : Wear suitable protective clothing.

- : Wear suitable gloves, suitable respiratory equipment.
- : Wear eye/face protection. Use shielding.



6. Accidental Release Measures

- | | |
|---------------------------|--|
| Personal Protection | : Avoid contact with skin and eyes. Eliminate sources of ignition. Take care of a good ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. |
| Environmental Precautions | : Use appropriate containment to avoid environmental contamination. |
| Methods for Cleaning Up | : Put outside in open air. Eliminate sources of ignition. Leave any ventilation switched on and vacate the area. Spillage should be soaked up in an inert, noncombustible absorbent material such as sand or earth (and minor traces washed away with plenty of water) Do not puncture or incinerate containers. Shovel up and place in sealed container for product recovery of safe disposal. |

7. Handling and Storage

- | | |
|-----------------------|---|
| Pressurized container | : Protect from sunlight and do not expose to temperatures exceeding 50 °C. : Do not pierce or burn, even after use. Keep out of the reach of children. Use with adequate ventilation. Do not inhale the spray particles. |
| Handling the product | : Keep away from food, drink and animal feeding stuffs. : Do not eat, drink and do not smoke in areas where product is used |
| Storage | : A cool, dry ventilated place (free from Frost). Do not |

Sprayway 955 Anti Static Spray (554ml)

store above 50°C. Keep away from heat, open flame, sparks, direct sunlight. Dropping containers may cause bursting.

8. Exposure Controls / Personal Protection

8.1. Respiratory protection

Use in a well-ventilated place.

Do not inhale the spray particles.

In case of insufficient ventilation : Wear suitable respiratory equipment.

8.2. Hand protection

Chemical resistant gloves are optional.

After use : Wash hands with water and soap.

8.3. Eye protection

Avoid contact with the eyes.

Do not spray in the direction of the eyes.

Chemical safety glasses are recommended.

8.4. Skin protection

Wear impervious clothing to prevent contact. Wash skin afterwards with water and soap.



9. Physical and Chemical Properties

| | |
|---------------------------------|-----------------------|
| Appearance | : Pressurized liquid |
| Odour | : Alcoholic odor |
| pH | : Not applicable |
| Boiling point and melting point | : Not applicable |
| Flash point | : < 0°C |
| Flammability | : Extremely flammable |
| Density | : 0.7164 g/ml |
| Solubility in water | : Soluble |

10. Stability and Reactivity

| | |
|---------------------|---|
| Stability | : Stable under normal conditions |
| Conditions to avoid | : Avoid elevated temperatures, flames, incandescent material. |



Mansion Close
Moulton Park
Northampton, NN3 6RU
Emergency Contact No:
0800 8405505

Date of issue SDS: 29/09/09
Review date SDS:
SDS Version: 1.1
MSDS Ref : 28

Sprayway 955 Anti Static Spray (554ml)

| | |
|--------------------------|---|
| Incompatibility | : Acetyl chloride and a wide range of oxidizing agents, heat and open flame. |
| Haz Decomp Products | : CO ₂ , CO and additional chemicals may be formed in small amounts. |
| Hazardous polymerization | : Oxides of carbon |

11. Toxicological Information

| | |
|-----------------------------------|---|
| Inhalation of high concentrations | : Pain in the throat, coughing, headache, dizziness, dullness, problems with breathing, may cause heart irregularities. |
| Contact with skin | : Repeated contact can cause irritation. |
| Contact with eyes | : Spraying into the eyes causes irritation. |
| Ingestion | : Stomach ache, nausea, vomiting, feeling sleepy, diarrhea |

12. Ecological information

Does not attack the ozone layer.

13. Disposal considerations

Dispose in accordance with local and state regulations.
No additional information available

14. Transport information

| | |
|----------------------|------------------|
| Proper shipping name | : AEROSOL |
| ADR/RID class | : 2 ADR 5F |
| IMCO | : Class 2 (2102) |
| EmS | : 2-13 |
| MFAG | : 620 |
| UN | : 1950 |
| Flash Point | : < 0 °C |

15. Regulatory information

Label according to the Directives relating to the classification, packaging and labeling of dangerous substances and preparations :

Sprayway 955 Anti Static Spray (554ml)

Extremely flammable

Risk phrases :

R : Extremely flammable



Safety phrases

: Pressurized container : protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition. No smoking.
S 2 : Keep out of the reach of children.
S 51 : Use only in well-ventilated areas.
S 23 : Do not breathe spray particles

16. Other information

SEE LABEL

REACH Disclaimer:

This information is based on current knowledge. Consistency of data in the SDS with CSR is considered, as far as the information is available at the time of compilation (cfr Revision date and Version number).

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.